



WeldTech 8000

Heating element butt welding machine for pipes and fittings out of polyolefines from 450mm up to 2000mm mm for the use on building sites and in trenches. The machine has a double clamping system on both the tight and movable side that are placed on two guiding shafts. For an easy and fast erection resp. Dismantling upon maintaining, the hydraulic cylinders are screwed next to the guiding shaft. Two flexible hoses with quick-action coupling enable the connection to the hydraulic controlling device. The double clamping tools are screwed to the steel pipe sub-construction. The external tight clamping tool can be dismantled easily by removing seven screws in order to weld at difficult accessible places like trenches or at branches of T-pieces. The electric hydraulic unit for the movement of the right double clamping device and for the exact control of the welding forces has a post-pressure facility to support these forces while cooling down and two quick-action couplings. The planer is fixed to the guiding shafts, has a chain drive in a closed aluminium housing with a gear motor and an automatic chip removal. The heating element is fixed to the guiding shafts, anti-stick coated, has an electronic temperature control with display, controlling lamps, an on/off switch and a connecting cable with shock-proof plug. For the heat-protected storage of the heating element and the planer, a reception box is available. Smaller pipe dimensions can be clamped by means of reducer inserts depending on the pipe diameter. A lift-off device for the easy inserting and removing of the heating element and the planer is available. All components are covered by the WeldTech works warranty. The WeldTech welding machine can easily be equipped subsequently with the WeldTech SPA weld log recorder (see page 20) and can also be supplied in CNC controlled version (see page 21). The SIMTECH welding machine has a voltage of 400 V. Other voltages on request.

Set composition

Description	Qty.	kg	Order-no.
basic machine with pipe clamping device and hydraulic hoses	1		
planer 400 V/1650 W	1		
hydraulic aggregate 400 V/1100 W	1		
heating element with temperature control and connection plug 400 V/7000 W	1		
heat-protected box for planer and heating element	1		
reducer inserts with screws (1 set = 8 halfshells) for each machine type			
lift-off device consisting of: gallows	1		
chain draft 400 V/200 W	1		

Please contact us for more detailed information.