WeldTech - Fusion Welding Equipment

WeldTech 3500





WeldTech 3500

Welding machine for heating element socket welding of PE, PP, PB, and PVDF Pipe and fittings from 20mm up to 110/ 125mm. The machine is mounted on a solid frame. The motion of the slides is controlled by a rack-and-pinion mechanism. Due to the steplessly adjustable prismatic clamping all outside diameters can be fixed. On the pipe side there is a double prism, on the fitting side there is an insertion stop. The penetration depth is secured by a turning button depending on the diameters. Both sides can be aligned in the axial plane for adjustment of the parts to be welded. The positioning is made by means of an insertion stop. The heating element holder for the socket heating element (230 V/1400 W), which can be swivelled in, is built on the machine. In connection with a table locking device it can be taken out of the holder and used as a hand heating element. With on/off switch, electronical adjustment and control of the temperature in accordance with DVS 2208. Machine version also available in inches, °F and 110 V.

As WeldTech 3600 the machine has a diameter up to $6^{\prime\prime}$ (160 mm).

| Set composition | | | |
|---|--------------------------------------|--|--|
| Description | Qty. | kg | Order-no. |
| Basic machine with heating element (230 V/50 Hz), electronically con- trolled and prismatic clamping tools OD 110 OD 125 | 1 | 35.0 | 3720220 3740230 |
| Table locking device | 1 | 1.0 | 371520 |
| Spigot and socket OD 20, Silverstone Spigot and socket OD 25, Silverstone Spigot and socket OD 32, Silverstone Spigot and socket OD 40, Silverstone Spigot and socket OD 50, Silverstone Spigot and socket OD 63, Silverstone Spigot and socket OD 75, Silverstone Spigot and socket OD 90, Silverstone Spigot and socket OD 110, Silverstone Spigot and socket OD 110, Silverstone Spigot and socket OD 125, Silverstone | 1 1 1 1 1 1 1 1 | 0.1 0.2 0.4 0.3 0.4 0.7 0.8 1.6 2.2 2.5 | HD020S HD025S HD032S HD040S HD050S HD063S HD075S HD090S HD110S HD125S |
| Cheese head screw M 8 x 50 Disc M 8 Spring washer M 8 Nut M 8 Socket wrench opening 13 mm Allen key, size 5 Allen key with T-handle, size 5 | 3 3 3 1 1 1 | 0.1 0.05 0.05 0.05 0.1 0.05 0.05 0.1 | 091H050 0125H 0127H 0934H ZRS13 ZIG05 ZIG03 ZIT05 |
| Transport and mounting crate (approx. 850 x 600 x 680 mm) | 1 | 41.0 | TK0075 |
| Pipe chamfering device, size 2 | 1 | 1.5 | W510300 |
| Pipe cutter, size 2 Pipe cutter, size 1 | 1 | 1.5 0.7 | W550110 W550100 |